

DEN NATIONALE Udstyrsbank

MARS NR.

MARS-22

BETEGNELSE

Tobii Pro3 glasses

SPECIFIKATIONER

Material Grilamid plastic, stainless steel, optical-grade plastic lenses

Scene camera format and resolution 1920 x 1080 @25 fps

Scene camera, field of view (diagonal) 106 deg. 16:9 format

Frame dimensions 153 x 168 x 51 mm

Audio 16-bit mono, integrated microphone

Number of eye tracking sensors 4 sensors (2 per eye)

Sensors ST™ LSM9DS1 sensors: Gyroscope and Accelerometer (sampled at 100 Hz); Magnetometer: (sampled at 10 Hz)

Weight 76.5 grams (including cable)

Nose pads Grilamid plastic, with clip-on attachments

Scene camera, video format H.264

Scene camera, field of view (horizontal and vertical) 95 deg. horizontal / 63 deg. vertical

Cable length 1200 mm

Fixed geometry Yes

Input voltage and current rating 5.5Vdc max, 0.5A

ANVENDELSE

Tobii Pro Glasses 3 are designed for versatility. That means they work as well in a car as a classroom, collecting first-hand attention data without missing a beat. It's the wearable eye tracker of choice for thousands of scientific researchers, marketers, UX designers, and manufacturers across the world.

BILLEDE

